

Split Phase Rigid Base Motors

These motors are Discontinued


- Features:** Class "B" Insulation • Continuous Duty • Open Construction
 • Reversible • Sleeve & Ball Bearing • 60 HZ



OS2014L

HP	RPM	Volts	F.L. Amps	S.F.	Frame	Stock Number	Bearings	Protector	Approx. "C"	Dim. "AG"	Enclosure	Conn. Dia.	Notes
1/6	1725	115	4.0	1.35	48	OS2014L	Sleeve	None	8.9	7.0	Open	39	
1/4	1725	115	4.6	1.35	48	OS2024L	Sleeve	None	9.15	7.3	Open	39	
		115	4.6	1.35	48	OB2024L	Ball	None	9.15	7.3	Open	39	
1/3	1725	115	6.2	1.0	48	OS2030L	Sleeve	None	9.4	7.5	Open	39	
		115	6.2	1.0	48	OS2030	Sleeve	Auto	9.4	7.5	Open	39	
		115	6.2	1.0	56Z	OS2031L	Sleeve	None	9.4	7.9	Open	39	1
1/2	1725	115	8.3	1.0	56	OS2050L	Sleeve	None	10.3	8.1	Open	39	

Notes:
 1. 56Z = 1/2" flat x 1-1/2" shaft, 3-1/2" shaft height
 See page 159 for mounting dimensions



Shaft Dimensions
 48 = 1/2" Flat x 1-5/8"
 56 = 5/8" Keyed x 1-7/8"