

48 & 56 Frame Split Phase Motors

C-Face Ventilator Motors

Split Phase — Dripproof — Round Frame

1800, 1200, 900, & 1800/1200 RPM — 1/8 thru 1/2 Hp

Features: Ball Bearing • 60 Hz • 40°C Ambient • Class B Insulated • Reversible

Applications: Designed for use on commercial and industrial ventilation systems.



F276

Stock No.	Hp	RPM	Volts	Frame	Overload Protector	Shaft Length	Service Factor	Full Load Amps	Notes
F270	1/8	1140	115	56CZ	Auto	2.25	1.40	3.0	
F271	1/6	1140	115	56CZ	Auto	2.25	1.35	3.6	
F250	1/4	1725	115	48CY	None	2.25	1.35	5.4	1
F273	1/4	1140	115	56CZ	Auto	2.25	1.35	5.0	
F274	1/4	850	115	56CZ	Auto	2.25	1.35	6.2	
F251	1/3	1725	115	48CY	None	2.25	1.35	5.8	1
F276	1/3	850	115	56CZ	Auto	2.25	1.00	8.6	
F252	1/3-1/9	1725/1140	115	56CZ	None	2.25	1.35	5.0/3.0	
F262	1/3-1/9	1725/1140	115	56CZ	Auto	2.25	1.35	5.4/2.3	
F263	1/2-1/6	1725/1140	115	56CZ	Auto	2.25	1.25	6.8/3.8	

Notes:

1. 56 C-Face and shaft on 48 Frame stator

For NEMA Standard Motor Dimensions, See Page 159