

Three Phase ODP Rigid Base Motors


- Features:**
- Ball Bearing • Continuous Duty Construction
 - Heavy Duty Steel • Open Drip Proof • 40° C Ambient
 - 60 HZ



BR3204VI

| HP | RPM | Volts | F.L. Amps | S.F. | Frame | Stock Number | Equiv- alent | Protector | Approx. "C" | Dim. "AG" | N.P. Eff. % | Conn. Dia. | Notes |
|-------------|-------------|-------------|-----------|-------------|---------|--------------|-----------------|-----------|----------------|--------------|----------------|---------------|-------|
| 1/3 | 1725 | 200-230/460 | 1.9/1.0 | 1.35 | 56 | OB3035 | | None | 10.8 | 8.6 | 69 | 34 | |
| 1/2 | 1725 | 200-230/460 | 2.6/1.3 | 1.25 | 56 | OB3055 | | None | 10.3 | 8.1 | 69 | 34 | |
| 3/4 | 1725 | 200-230/460 | 3.1/1.6 | 1.25 | 56 | OB3075 | | None | 10.3 | 8.1 | 72 | 34 | |
| 1 | 1725 | 200-230/460 | 3.6/1.8 | 1.15 | 56 | OB3104 | | None | 11.3 | 9.1 | 76 | 34 | |
| | | 200-230/460 | 3.6/1.8 | 1.15 | 56HZ | OB3104VI | | None | 12.2 | 10.0 | 76 | 34 | 1 |
| | | 208-230/460 | 4.3/2.2 | 1.3 | 56H | BR3104 | OB3104A | Auto | 13.2 | 11.0 | | 28 | 3 |
| | | 208-230/460 | 3.6/1.8 | 1.25 | 56H | OB3104A | | Auto | 11.75 | 9.75 | | 35 | |
| 1-1/2 | 3450 | 200-230/460 | 3.8/1.9 | 1.15 | 56HZ | OB3152VI | | None | 12.2 | 9.6 | 84 | 34 | 1 |
| | | 208-230/460 | 4.1/2.05 | 1.3 | 56H | BR3152 | | Auto | 13.7 | 11.5 | | 28 | |
| | 1725 | 200-230/460 | 5.8/2.9 | 1.15 | 56 | OB3154 | | None | 12.3 | 10.1 | 74 | 34 | |
| | | 200-230/460 | 4.6/2.3 | 1.15 | 56HZ | OB3154VI | | None | 12.2 | 10.6 | 82 | 34 | 1 |
| | | 208-230/460 | 4.4/2.2 | 1.2 | 56HZ | BR3154 | OB3154A | Auto | 14.6 | 12.0 | | 28 | 1,3 |
| | | 208-230/460 | 5.0/2.5 | 1.15 | 56HZ | OB3154A | | Auto | 12.25 | 2.25 | | 35 | |
| | | 208-230/460 | 5.0/2.5 | 1.15 | 56H | BR3155 | OB3155A | Auto | 13.2 | 11.0 | | 28 | 3 |
| | | 208-230/460 | 4.6/2.3 | 1.15 | 56H | OB3155A | | Auto | 11.75 | 9.75 | | 35 | |
| 2 | 3450 | 200-230/460 | 5.2/2.6 | 1.15 | 56H | OB3202 | | None | 12.8 | 10.6 | 86 | 34 | |
| | | 200-230/460 | 5.0/2.5 | 1.15 | 56HZ | OB3202VI | | None | 13.2 | 10.6 | 85 | 34 | 1 |
| | 1725 | 208-230/460 | 5.2/2.6 | 1.2 | 56H | BR3202 | | Auto | 13.7 | 11.5 | | 28 | |
| | | 200-230/460 | 6.0/3.0 | 1.15 | 56H | OB3204 | | None | 12.3 | 10.1 | 78 | 34 | |
| | | 200-230/460 | 6.8/3.4 | 1.15 | 56HZ | OB3204VI | | None | 13.2 | 10.6 | 78 | 34 | 1 |
| | | 208-230/460 | 6.0/3.0 | 1.15 | 56HZ | BR3204V1 | OB3204A | Auto | 14.1 | 11.5 | | 28 | 1,3 |
| | | 208-230/460 | 6.2/3.1 | 1.15 | 56HZ | OB3204A | | Auto | 13.25 | 11.0 | | 35 | |
| | | 3 | 3450 | 200-230/460 | 7.2/3.6 | 1.15 | 56HZ | OB3302VI | | None | 13.2 | 10.6 | 85 |
| 208-230/460 | 8.0/4.0 | | | 1.15 | 56HZ | BR3302 | | Auto | 14.1 | 11.5 | | 28 | 1 |
| 1725 | 200-230/460 | | 8.6/4.3 | 1.15 | 56HZ | OB3304VI | | None | 14.0 | 11.4 | 79 | 34 | 1 |
| | 200-230/460 | | 8.6/4.3 | 1.15 | 56HZ | OB3304 | | None | 14.0 | 11.8 | 79 | 34 | 2 |
| 5 | 3450 | 208-230/460 | 9.0/4.5 | 1.25 | 56HZ | BR3304V1 | H887 | Auto | 15.1 | 12.5 | | 28 | 1,3 |
| | | 208-230/460 | 12.2/6.1 | 1.15 | 56HZ | BR3502 | | Auto | 15.6 | 13.0 | | 28 | 1 |

- Notes:**
1. 56HZ = 7/8" x 2-5/16" shaft
 2. 56HZ = 3/4" x 2-3/8" shaft
 3. Disc. when stock is depleted
- See page 159 for mounting dimensions



Shaft Dimensions
 56 = 5/8" Keyed x 1-7/8"
 56H = 5/8" Keyed x 1-7/8"