

# 5-5/8" Diameter Stock Motors

## Unit Heater Fan Motors

- Permanent Split Capacitor – 60 Hz
- Thermally Protected
- Sleeve & Ball Bearing Models
- Continuous Duty, Air Over



136, 749,  
750, 751



177, 183, 397, 566,  
730, 731, 732, 733,  
734, 767, 768, 769

Stock.													Shaft Dia.	Iron	Conn.
No.	Rotation	Hp	Volts	RPM	Amps	Speeds	Capacitor	Construction	Base	"A"	& Length	Stack	Dia. No.*	Notes	
177	CWSE	1/6	115	1075	2.5	1	FURNISHED	TE	CUSHION	3-1/2	1/2 x 5	1			
749	CWSE	1/6	115	1075	2.6	1	FURNISHED	TE	NONE	4-1/4	1/2 x 4	1			
136	REV	1/6-1/8	115	1075	2.5-1.7	2	7.5MFD-370V	TE	NONE	3-3/4	1/2 x 5-1/2	1	41u	1	
730	REV	1/6	115/208-230	1140	2.4/1.2	1	FURNISHED	TE	CUSHION	6	1/2 x 4-1/2	1-1/2	70u	1.2	
566	CWSE	1/4	115	1075	3.2	1	FURNISHED	TE	CUSHION	4-1/4	1/2 x 5	1-1/2			
750	CWSE	1/4	115	1075	4.1	1	FURNISHED	TE	NONE	4-1/4	1/2 x 4	1-1/2			
734	CWSE	1/4	115	1140	5.0	1	FURNISHED	TE	CUSHION	5	1/2 x 3	2			
731	REV	1/4	115/208-230	1140	3.8/1.9	1	FURNISHED	TE	CUSHION	6-1/4	1/2 x 4-1/2	1-3/4	70u	1.2	
767	REV	1/4	115/230	1725	3.4/1.7	1	FURNISHED	TE	CUSHION	6-3/4	1/2 x 4-1/2	2		1.2	
183	CWSE	1/3	115	1075	4.8	1	FURNISHED	TE	CUSHION	4-1/4	1/2 x 5	1-3/4		1	
751	CWSE	1/3	115	1075	5.1	1	FURNISHED	TE	NONE	4-1/4	1/2 x 4	1-3/4			
397	REV	1/3	230	1100	2.5	1	FURNISHED	OLE	CUSHION	5	1/2 x 6	2	19u	1	
732	REV	1/3	115/208-230	1140	4.8/2.4	1	FURNISHED	TE	CUSHION	6-1/2	1/2 x 4-1/2	2-1/4	70u	1.2	
768	REV	1/3	115/230	1725	3.8/1.9	1	FURNISHED	TE	CUSHION	6-3/4	1/2 x 4-1/2	2		1.2	
733	REV	1/2	115/208-230	1140	5.6/2.8	1	FURNISHED	TE	CUSHION	7-1/4	1/2 x 4-1/2	2-1/2	70u	1.2	
769	REV	1/2	115/230	1725	5.0/2.5	1	FURNISHED	TE	CUSHION	7-1/2	1/2 x 4-1/2	2-3/4		1.2	

## Heating & Refrigeration Motors

Permanent Split Capacitor – 60 Hz – Continuous Duty, Air Over

OEM replacement for American Air Filter, Copeland, Herman-Nelson, Hussman, Larkin Coil



639, 946



0547, 9609, 9610



174



992

Stock No.	Hp	Volts	RPM	Amps	Rotation		Capacitor	"A"	Shaft Diameter & Length	Iron Stack	Connection Diagram	
					Shaft End	Capacitor					No.*	Notes
0547	1/8	115	700	2.5	CCW	FURNISHED	6	1/2 x 1-3/4	1-3/4			1,3
9609	1/8	208-230	700	1.2	CCW	FURNISHED	6	1/2 x 1-3/4	1-3/4			1,3
9610	1/4	115	825	5.4	REV	FURNISHED	5-3/4	1/2 x 2	2			1,3
946	1/10	115	1075	1.8	CCW	5MFD-370V	3-1/2	1/2 x 2	3/4		4u	4
639	1/10	208-230	1075	.7	REV	5MFD-370V	3-1/2	1/2 x 2	3/4		4u	4
992	1/2	208-230	1075	4.8	REV	7.5MFD-370V	6-3/4	1/2 x 3	2-1/2			1,4
174	1/6	208-230	1625	1.0	REV	5MFD-370V	4	1/2 x 2-1/2	1		17u	4

### Notes:

1. Ball Bearing
  2. Includes split bushing and key for 5/8" shaft
  3. Supplied with Lead & Plug Assembly
  4. Special OEM Replacement Motor (See Pages 97-122)
- \*See Pages 160-163 for Connection Diagram