

5-5/8" Diameter Single Shaft Fan/Blower Motors

Furnaces - Air Handlers - Fan Coils

Features

- Auto Protector
- Continuous Air Over
- Energy Efficient s
- Multiple Mount
- Open Construction
- Sleeve Bearing
- 1/2" Dia. - Flatted Shaft
- 26" Leads (Minimum)
- 48 Frame (5-5/8" Dia.)
- 40° C Ambient
- 60 HZ only




HI EFFICIENCY - PSC - CAPACITOR INTERNALLY MOUNTED

HP	RPM/ Speeds	Volts	Rated	Amps Max.	Stock Number	Rotation	Ring* Type	Dim. Ref.	Conn. Dia.	Notes
1/8	1050/3	115	2.2	2.4	FSP4006	CCWLE	B	1	103	S
1/8	1050/1	115	2.4	2.5	FSP4006S	CCWLE	B	2	93	S
1/5	1050/3	115	3.2	4.0	FSP4016	CCWLE	B	8	103	S
1/5	1050/3	208-230	1.5	2.0	FSP4016H	CCWLE	B	8	1	S
1/5	1050/1	115	3.2	4.0	FSP4016S	CCWLE	B	1	93	S
1/4	1050/3	115	3.3	3.6	FSP4026	REV.	B	3	102	S
1/4	1050/3	230	2.5	2.7	FSP4026H	CCWLE	B	3	1	S
1/4	1050/1	115	4.0	4.2	FSP4026S	CCWLE	B	4	93	S
1/4	1050/1	230	2.4	2.5	FSP4026SH	CCWLE	B	5	93	S
1/3	1050/3	115	6.0	6.4	FSP4036	CCWLE	B	6	103	S
1/3	1050/4	115	5.7	6.0	OCB4036SP	CCWLE	-	7	2	1 S

Notes:

1. No resilient rings. 12" leads with Molex terminal.
- * For ring type see page 155



Approximate Dimensions

Ref.	BM	R	C	N	T
1	4-3/8	4-15/16	9-5/8	4-3/4	-
2	4-3/8	4-15/16	10-5/16	5-7/16	5/8
3	5	5-1/2	11	5-1/2	5/8
4	4-7/8	5-3/8	10-7/8	5-1/2	1/2
5	4-3/4	5-5/16	10-3/4	5-1/2	1/2
6	5-3/8	5-15/16	10-5/8	4-3/4	-
7	5-3/8	-	10	4-5/8	-
8	4-3/8	4-15/16	9-5/8	4-1/4	-