

5-5/8" Diameter Totally Enclosed Outdoor Sleeve Bearing Fan Motors

Condensers - Heat Pump - Refrigeration

Features

- All Angle Mount
- Auto Protector
- Class "B" Insulation
- Energy Efficient S
- Ext. Thru Bolts - Both Ends
- Permanent Split Capacitor
- Reversing Plug
- Sleeve Bearing
- 1/2" Dia. Shaft - Dbl. Flat
- 4, 6 & 8-Pole
- 26" Leads
- 48 Frame (5-5/8" Dia.)
- 60° C Ambient
- 60 HZ



"TURN-A-BOU" 1 AND 2-SPEED (CAPACITOR NOT INCLUDED)

HP	RPM/ Speeds	Volts	Amps		Stock Number	Capac.	Dim. Ref.	Conn. Dia.	Notes	
			Rated	Max.						
1/6	1075/2	208-230	.9	1.3	FSE1016	5/370V	1	16		\$
1/6	1075	208-230	.9	1.3	FSE1016S	5/370V	1	15	2 Discontinued	\$
1/6	1075	208-230	.9	1.3	FSE1016SVI	5/370V	1	64	1	\$
1/4	1075/2	208-230	1.3	1.8	FSE1026	5/370V	2	16		\$
1/4	1075	208-230	1.3	1.8	FSE1026S	5/370V	2	15	2 Discontinued	\$
1/4	1075	208-230	1.3	1.8	FSE1026SVI	5/370V	2	64	1	\$
1/4	1075/2	277	1.3	1.8	7FSE1026	5/370V	2	16		\$
1/3	1075/2	208-230	1.8	2.8	FSE1036	7.5/370V	3	16		\$
1/3	1075	208-230	1.8	2.8	FSE1036S	7.5/370V	10	15	2 Discontinued	\$
1/3	1075	208-230	1.8	2.8	FSE1036SVI	7.5/370V	10	64	1	\$
1/2	1075/2	208-230	2.8	4.0	FSE1056	10/370V	4	16		\$
1/2	1075	208-230	2.8	4.0	FSE1056S	10/370V	11	15	2 Discontinued	\$
1/2	1075	208-230	2.8	4.0	FSE1056SVI	10/370V	11	64	1	\$
1/2	1075/2	277	2.4	3.2	7FSE1056	10/370V	4	16		\$
3/4	1075	208-230	4.9	5.2	FSE1076S	15/370V	5	64	2 Discontinued	\$
3/4	1075	208-230	4.2	5.2	FSE1076SVI	15/370V	5	64	1	\$

2-SPEED

HP	RPM/ Speeds	Volts	Amps		Stock Number	Capac.	Dim. Ref.	Conn. Dia.	Notes	
			Rated	Max.						
1/4	1625/2	208-230	1.7	2.5	FSE1024	5/370V	6	16		\$
1/2	1625/2	208-230	3.0	4.2	FSE1054	5/370V	7	16		\$

SINGLE SPEED

HP	RPM	Volts	Amps		Stock Number	Capac.	Dim. Ref.	Conn. Dia.	Notes	
			Rated	Max.						
1/6	825	208-230	1.1	1.6	FSE1018S	5/370V	12	15		\$
1/4	825	208-230	1.5	1.9	FSE1028S	5/370V	13	15		\$
1/3	825	208-230	1.8	2.4	FSE1038S	7.5/370V	8	15		\$
1/2	825	208-230	2.7	3.7	FSE1058S	10/370V	9	15		\$

Notes:

1. 1/2" hub on shaft end frame with slinger. Grommet on lead exits.
2. Item to be discontinued when stock is depleted.

Approximate Dimensions

Ref.	BM	C	N
1	3-15/16	9-15/16	6
2	4-5/16	10-5/16	6
3	4-13/16	10-13/16	6
4	5-5/16	11-5/16	6
5	5-5/8	12-1/16	6-7/16
6	4-11/16	10-11/16	6
7	5-3/8	11-3/8	6
8	5-3/16	11-3/16	6
9	5-11/16	11-11/16	6
10	4-7/8	10-7/8	6
11	5-3/8	11-3/8	6
12	4-3/16	10-3/16	6
13	4-15/16	10-15/16	6

