

# Century® and Universal Electric™ Hot Water Circulator Pump Motors

## 60 Hz • Open Dripproof • 1725 RPM • 1/12 thru 3 HP

**Features:** Single and Three Phase • Special Red Paint • Bell and Gosset, S.A. Armstrong, TACO, Replacement Motors • Cushion Ring, Round Frame

**Applications:** Replacement motor to be used on hot water pumps.



939

HP	Volts	Frame	Full Load Amps	Service Factor	Overload Protector	Bearings	Stock Number	XE Hub-Hub	Notes
<b>TACO - SINGLE PHASE - 1800 RPM - ROUND FRAME - CUSHION RING-DRIPPROOF</b>									
1/2	115/230	56Y	7.2/3.6	1.25	Auto	Sleeve	C240	9.12	1
3/4	115/230	56Y	10.4/5.2	1.30	Auto	Sleeve	C244	9.63	1
1	230/115	56Y	6.5/13.0	1.25	Auto	Sleeve	C247	9.80	1
1-1/2	230/115	56Y	7.5/15.0	1.20	Auto	Ball	C248	10.60	1
<b>ARMSTRONG - SINGLE PHASE - 1800 RPM - ROUND FRAME - CUSHION RING-DRIPPROOF</b>									
1/2	115/230	56Y	7.3/3.6	1.25	Auto	Sleeve	C242	9.93	1
3/4	115/230	56Y	10.4/5.2	1.30	Auto	Sleeve	C233	9.93	1
1	230/115	56Y	13.0/6.5	1.25	Auto	Sleeve	C245	9.93	1
<b>BELL AND GOSSET - SINGLE PHASE - 1800 RPM - ROUND FRAME - CUSHION RING-DRIPPROOF</b>									
1/2	115	48Y	1.75	1.00	Auto	Sleeve	939	8.29	Discontinued Use OTA2004
1/8	115	48Y	2.6	1.00	Auto	Sleeve	940	8.29	1,2
1/6	115	48Y	2.8	1.00	Auto	Sleeve	941	8.29	1,2
1/2	115/230	56Y	9.6/4.8	1.25	Auto	Sleeve	C241	9.17	1
3/4	115/230	56Y	11.8/5.9	1.25	Auto	Sleeve	C243	9.15	1
1	230/115	56Y	6.5/13.0	1.25	Auto	Sleeve	C246	9.52	1
<b>TACO - THREE PHASE - 1800 RPM - ROUND FRAME - CUSHION RING-DRIPPROOF</b>									
1/2	200/230/460	56Y	1.8-2.2/1.1	1.25	None	Sleeve	H981	9.63	1
3/4	208-230/460	56Y	2.5-2.6/1.3	1.30	None	Sleeve	H982	9.63	1
1	208-230/460	56Y	3.4-3.4/1.7	1.25	None	Sleeve	H946	9.63	1
1	575	56Y	1.4	1.25	None	Sleeve	H947	9.63	1
1-1/2	208-230/460	56Y	4.8-5.0/2.5	1.20	None	Ball	H945	10.10	1
2	208-230/460	56Y	6.3-6.4/3.2	1.15	None	Ball	H987	9.93	1
3	460/208-230	56Y	4.4/9.0-8.8	1.15	None	Ball	H988	12.04	1
<b>ARMSTRONG - THREE PHASE - 1800 RPM - ROUND FRAME - CUSHION RING-DRIPPROOF</b>									
3/4	208-230/460	56Y	2.5-2.6/1.3	1.25	None	Sleeve	H989	9.08	1
1	208-230/460	56Y	3.4-3.4/1.7	1.25	None	Sleeve	H984	10.07	1
1-1/2	208-230/460	56Y	4.8-5.0/2.5	1.15	None	Sleeve	H986	9.82	1
<b>BELL AND GOSSET - THREE PHASE - 1800 RPM - ROUND FRAME - CUSHION RING-DRIPPROOF</b>									
3/4	208-230/460	56Y	2.5-2.6/1.3	1.25	None	Sleeve	H983	9.08	1
1	208-230/460	56Y	3.4-3.4/1.7	1.25	None	Sleeve	H985	9.57	1
1-1/2	208-230/460	56Y	4.8-5.0/2.5	1.15	None	Sleeve	H986	9.82	1

**Notes:**

1. Hub-Hub dimension is the dimension from the center of the opposite shaft end hub to the outside of the shaft end hub. Hub-Hub Dimension is ±0.0625 Includes Mounting Bracket
2. Includes mounting bracket