

3.3" DIAMETER



Flue Exhaust and Draft Booster Blower Motors



Fig. A D408



Fig. B D454



Fig. C D455



Fig. D D456, D457, D458, D1174, D1171



Fig. E D1179, D1180



Fig. F D1190



Fig. G D1169



Fig. H D1167

- Thermally protected
- UL Recognized
- Supplied with bushings
- CSA Certified
- Supplied with Centrifugal Switch

SHADED POLE • OPEN VENTILATION								
H.P.	Volts	Amps	RPM	Rot.	Model	Fig.	A Dim.	Shaft Dim.
1/150	115	.5	3000	C.W.	D408★	A	5½	¼ x 1½
1/40	208/230	.55	3000	C.C.W.	D1167	H	4⅞	⅝ x 1
1/30	115/230	1.3/1.7	3000	C.C.W.	D455•	C	5⅞	¼ x 3⅞
1/30	115	1.5	3000	C.W.	D454△	B	6⅜	¼ x 1½
1/15	115/230	2.0/1.0	3000	C.W.	D456#	D	6½	¼ x 2¾
1/15	208/230	1.0	3000	C.W.	D458#	D	6½	¼ x 2¾
1/15	115/230	2.0/1.0	3000	C.C.W.	D457#	D	6½	¼ x 2¾
1/15	460	.6	3000	C.W.	D1174•	D	6¾	¼ x 2½
1/15	460	.6	3000	C.C.W.	D1171•	D	6⅞	¼ x 2½
1/10	208-230	1.5	3000	C.C.W.	D1169	G	5¾	⅝ x 1

★ Drilled & Tapped Holes (No. 8-32NC) in face of case at shaft end for mounting in various Coleman mobile home furnace applications, also has mounting studs.

▲ Used in Economite, "E-20", LS1/Miller and Mid Continent gas units.

- Ball bearing motor
- # Stainless steel shafts


All models with ¼" diameter shafts include a shaft bushing.

NOTE: Rotation is determined by looking at shaft end. Shaft length is measured from motor face.

- Thermally protected
- UL Recognized
- CSA Certified

SHADED POLE • OPEN VENTILATION								
H.P.	Volts	Amps	RPM	Rot.	Model	Fig.	A Dim.	Shaft Dim.
1/30	115	1.5	3000	C.W.	D1179#	E	3½	⅝ x 2⅞
1/30	115	1.6	3300	C.W.	D1190#	F	4⅞	⅝ x 1¾
1/20	115	1.5	3300	C.W.	D1180#	E	3⅝	⅝ x 2⅞

Stainless steel shafts



Products on this page are NOT SUITABLE for unattended equipment unless indicated by ► symbol. See inside back cover for additional information.

See pages 48 through 71 for OEM direct replacement models.