



Fig. A D242, D340



Fig. B D143



Fig. C D140, D144



Fig. D D148



Fig. E D142



Fig. F D260, D261



Fig. G D240



Fig. I D1038



Fig. K D1054



Fig. M D1028



Fig. H D342, D1036



Fig. J S156



Fig. L D1066

- 115 VAC models
- Thermally protected
- UL recognized

ROOF TOP VENTILATORS • SHADED POLE OPEN AND TOTALLY CLOSED VENTILATION • AIR-OVER									
H.P.	Volts	Amps	RPM	Rot.	Model	Fig.	Const.	"A" Dim.	Shaft Dim.
1/40	115	1.1	1050	C.W.	D340*	A	Closed	2 ⁵ / ₈	3 ³ / ₈ x 2 ⁵ / ₈
1/30-1/40	115	1.5-1.0	1050	C.C.W.	D143‡	B	Open	2 ¹ / ₄	1 ¹ / ₂ x 1 ⁵ / ₈
1/25	115	1.4	1125	C.W.	D1038	I	Open	4	1 ¹ / ₂ x 2 ¹ / ₂
1/20	115	1.95	1050	C.W.	D1036°	H	Open	2 ³ / ₈	3 ³ / ₈ x 2 ¹ / ₈
1/15	115	2.3	1050	C.W.	D342*	H	Open	2 ⁹ / ₁₆	3 ³ / ₈ x 2 ¹ / ₂
1/15	115	2.7	1050	C.W.	D140✓	C	Open	2 ⁵ / ₈	3 ³ / ₈ x 2 ³ / ₈
1/15-1/25	115	2.6-1.6	1050	C.W.	D142	E	Open	2 ¹ / ₄	3 ³ / ₈ x 2 ³ / ₈
1/12-1/20-1/25	115	3.1-2.1-1.5	1050	C.W.	D1054■	K	Open	2 ⁵ / ₈	1 ¹ / ₂ x 2 ¹ / ₂
1/10	115	3.6	1050	C.W.	D148	D	Open	2 ⁵ / ₈	3 ³ / ₈ x 3 ¹ / ₂
1/10	115	3.6	1050	C.W.	D144	C	Open	2 ⁵ / ₈	1 ¹ / ₂ x 4 ¹ / ₂
1/10	115	3.6	1050	C.W.	D1066	L	Open	3 ⁷ / ₈	1 ¹ / ₂ x 2 ³ / ₄
1/8	115	3.3	1050	C.W.	D1028	M	Open	3 ¹ / ₂	1 ¹ / ₂ x 2 ¹ / ₂
1/6	115	6.2	1050	C.W.	D240#	G	Open	4	1 ¹ / ₂ x 3 ¹ / ₂
1/6	115	6.6	1050	C.W.	S156	J	Open	3 ¹ / ₂	1 ¹ / ₂ x 3 ⁷ / ₈

* With plug for Penn Ventilator

‡ Repl. for Siegler & Williams Wall Heaters

Repl. for Leslie-Locke Roof Ventilator

° Penn Ventilator

✓ Repl. for Butler & Leslie-Locke Roof Ventilator—BX Connector

■ Hub only on shaft end


UNIT HEATERS SHADED POLE • TOTALLY ENCLOSED VENTILATION • AIR-OVER STERLING RADIATOR CO.									
H.P.	Volts	Amps	RPM	Rot.	Model	Fig.	"A" Dim.	Shaft Dim.	
1/20	115	2.0	1050	C.W.	D242	A	3 ¹ / ₈	3 ³ / ₈ x 3	

UNIT HEATERS PSC • TOTALLY ENCLOSED VENTILATION • AIR-OVER									
H.P.	Volts	Amps	RPM	Rot.	Model	Fig.	"A" Dim.	Shaft Dim.	
1/8-1/15	115	2.3-1.1	1075	Rev.	D261#	F	3 ⁵ / ₈	1/2 x 3	
1/6	115	2.9	1075	C.W.	D260#+	F	3 ⁷ / ₈	1/2 x 3	

+ Replacement for ITT REZNOR

4M 370V capacitor included.

NOTE: Rotation is determined by looking at shaft end. Shaft length is measured from motor face.



Products on this page are NOT SUITABLE for unattended equipment unless indicated by ▶ symbol. See inside back cover for additional information.

See pages 48 through 71 for OEM direct replacement models.