

MULTI-PURPOSE CONDENSER FAN & DIRECT DRIVE BLOWER MOTORS

CONDENSER FAN MOTORS • TOTALLY ENCLOSED AIR-OVER										
H.P.	Volts	Amps	CAP @ 208V Line	CAP @ 230V Line	RPM	Rot.	Model	Fig.	"A" Dim.	Shaft Dim.
1/3 1/4 1/5 1/6	208-230	1.9 1.5 1.2 1.0	10 MFD 10 MFD 10 MFD 10 MFD	7.5 MFD 7.5 MFD 7.5 MFD 7.5 MFD	825	Rev.	D2826•	A	5-1/4	1/2 x 5
1/3 1/4 1/5 1/6	208-230	2.6 2.5 2.0 1.8	7.5 MFD 7.5 MFD 7.5 MFD 7.5 MFD	5 MFD 5 MFD 5 MFD 5 MFD	1075	Rev.	D837	A	4-1/2	1/2 x 3-3/4
1/3 1/4 1/5 1/6	208-230	3.0 2.2 1.6 1.3	12.5 MFD 12.5 MFD 12.5 MFD 12.5 MFD	10 MFD 10 MFD 10 MFD 10 MFD	1075	Rev.	D2827•	A	5-1/4	1/2 x 5

DIRECT DRIVE FAN & BLOWER MOTORS • OPEN DRIP PROOF											
H.P.	Volts	Amps	Cooling	Heating	Cap.	RPM	Rot.	Model	Fig.	"A" Dim.	Shaft Dim.
1/2 1/3 1/4 1/5 1/6	115	7.3 6.9 5.5 3.6 2.8	High High Med-Hi Med-Low Low	Med-Low Med-Low Low Low Low	10 MFD 5 MFD 5 MFD 5 MFD 5 MFD	1075	Rev.	D2835	B	4-3/4	1/2 x 5
1/2 1/3 1/4 1/5 1/6	208-230	3.6 3.5 2.8 1.9 1.3	High High Med-Hi Med-Low Low	Med-Low Med-Low Low Low Low	10 MFD 5 MFD 5 MFD 5 MFD 5 MFD	1075	Rev.	D833	B	4-3/4	1/2 x 5
3/4 1/2 1/3 1/4 1/5	115	8.1 6.6 4.6 3.8 3.1	High High Med-Hi Med-Low Low	Med-Low Low Low Low Low	20 MFD 10 MFD 10 MFD 10 MFD 10 MFD	1075	Rev.	D2832	C	5-3/4	1/2 x 5
3/4 1/2 1/3 1/4 1/5	208-230	3.8 3.7 2.5 1.8 1.7	High High Med-Hi Med-Low Low	Med-Low Low Low Low Low	20 MFD 10 MFD 10 MFD 10 MFD 10 MFD	1075	Rev.	D2833	C	5-3/4	1/2 x 5

• Ball bearing motor




Fig. A D2826, D837, D2827



Fig. B D833, D2835



Fig. C D2832, D2833



Products on this page are NOT SUITABLE for unattended equipment unless indicated by symbol. See inside back cover for additional information.

See pages 48 through 71 for OEM direct replacement models.

PSC motors use 5M 370V capacitors unless otherwise indicated.