



**Fig. A D802**



**Fig. B D1914**



**Fig. C D916, D918**



**Fig. D D921**



**Fig. E D920**



**Fig. F D960, D961**

### 460 VAC MOTORS

- Thermally protected
- Electrically reversible
- All angle mount bearings
- Ball bearings
- 60° ambient temperature rating

PSC • TOTALLY ENCLOSED • AIR-OVER								
H.P.	Volts	Amps	RPM	Load Factor	Model	Fig.	"A" Dim.	Shaft Dim.
1/2	460	1.0	1050	1.0	D802★•	A	5 1/2	1/2 x 3 1/3
3/4	460	1.7	1050	1.1	D1914★•	B	6	1/2 x 6

- ★ 10M 370V capacitor
- Ball bearing motor


- 230/460 and 460 VAC models
- Electrically reversible
- Thermally protected
- All angle mount bearings. Use rainshield when necessary
- Comes with unmounted conduit box
- Ball bearing and sleeve bearing models
- 60° ambient temperature rating

PSC • OPEN VENTILATION • AIR-OVER								
H.P.	Volts	Amps	RPM	Load Factor	Model	Fig.	"A" Dim.	Shaft Dim.
1/4-1/6	460	1.0-.6	1625	1.0	D918•	C	4 1/4	1/2 x 6 1/2
1/2-1/3	460	1.6-1.1	1625	1.3	D916+•	C	5 1/2	1/2 x 6 1/2

- + 7.5M 370V capacitor
- Ball bearing motor

PSC • OPEN VENTILATION • AIR-OVER								
H.P.	Volts	Amps	RPM	Load Factor	Model	Fig.	"A" Dim.	Shaft Dim.
1/3	460	1.3	825	1.3	D960•	F	5	1/2 x 6
1/3	230/460	2.7/1.4	825	1.3	D921•	D	5 1/4	1/2 x 6 3/8
1/2	460	1.9	825	1.3	D961+•	F	5 3/4	1/2 x 6
1/2	460	2.1	825	1.3	D920#†	E	5 1/2	1/2 x 4 1/2

- Ball bearing motor
- # 15M 370V capacitor
- + 7.5M 370V Capacitor
- † Doesn't come with conduit box



Products on this page are NOT SUITABLE for unattended equipment unless indicated by ► symbol. See inside back cover for additional information.

See pages 48 through 71 for OEM direct replacement models.

PSC motors use 5M 370V capacitors unless otherwise indicated.