



Fig. A D786, D789



Fig. B D781, D783, D784, D787, D788



Fig. C D780, D782, D785



Fig. D D770, D771, D773, D774, D775, D776, D777



Fig. E D772



Fig. F D778


- 208-230,230 and 115 VAC models
 - Thermally protected
 - UL recognized
 - CSA certified
 - All angle mount sleeve bearings
 - Single shaft motors are electrically reversible
 - These motors should **not** be used for replacements where original motor is rated below 1500 RPM.
- Some high slip air-conditioning motors are rated often at 1300-1400 RPM.

SINGLE SHAFT									
PSC • OPEN VENTILATION • AIR-OVER									
H.P.	Volts	Amps	RPM	Ld. Fac.	Model	Fig.	"A" Dim	Shaft Dim.	
1/4	115	3.5	1625	1.2	D782	C	4 1/4	1/2 x 6	
1/4	208-230	1.5	1625	1.2	D783	B	4	1/2 x 6	
1/3-1/4-1/6	115	4.7-3.5-2.7	1625	1.2	D780	C	4 1/2	1/2 x 6	
1/3	208-230	2.3	1625	1.2	D787	B	4 1/4	1/2 x 7	
1/3-1/4-1/6	208-230	2.0-1.6-1.2	1625	1.2	D781	B	4 1/2	1/2 x 7	
1/2-1/3-1/4	115	8.4-6.4-5.0	1625	1.4	D785	C	4 3/4	1/2 x 6	
1/2	208-230	3.9	1625	1.3	D788	B	5	1/2 x 6	
1/2-1/3-1/4	208-230	3.8-2.8-2.1	1625	1.3	D784	B	5	1/2 x 6	
3/4	208-230	5.2	1625	1.3	D789+	A	5 1/4	1/2 x 6	
3/4-1/2-1/3	230	5.3-3.8-2.9	1625	1.3	D786+	A	5 1/4	1/2 x 6	

+ 7.5M 370V capacitor

- Ideal versatility using Kit 200 "X" brackets to accommodate various cradle base lengths
- Ideal for lug mounting using lug Kit 55L or 55S

DOUBLE SHAFT									
PSC • OPEN VENTILATION • AIR-OVER									
H.P.	Volts	Amps	Rot.	RPM	Ld. Fac.	Model	Fig.	"A" Dim.	Shaft Dim.
1/5-1/8-1/10	115	2.8-2.0-1.6	D.S.	1625	1.0	D776	D	3 1/2	8 1/2 x 1/2 x 8 1/2
1/5-1/6-1/8	208-230	1.1-8-7	D.S.	1625	1.0	D775	D	3 1/2	8 1/2 x 1/2 x 8 1/2
1/4-1/5-1/6	115	3.8-2.8-2.1	D.S.	1625	1.3	D773	D	4	8 1/2 x 1/2 x 8 1/2
1/4-1/5-1/6	208-230	1.9-1.2-.9	D.S.	1625	1.3	D774	D	4	8 1/2 x 1/2 x 8 1/2
1/3-1/4-1/6	115	5.9-4.4-3.5	D.S.	1625	1.6	D770	D	4 1/2	8 3/4 x 1/2 x 8 3/4
1/3-1/4-1/6	208-230	2.4-1.8-1.4	D.S.	1625	1.4	D771	D	4 1/2	8 3/4 x 1/2 x 8 3/4
1/2-1/3-1/4	115	9.4-6.0-4.5	D.S.	1625	1.5	D777	D	5	7 1/2 x 1/2 x 7 1/2
1/2-1/3-1/4	208-230	3.8-2.8-2.1	D.S.	1625	1.3	D772	E	4 3/4	8 x 1/2 x 8
3/4-1/2-1/3	208-230	5.3-3.8-3.2	D.S.	1625	1.3	D778	F	5 1/4	7 1/2 x 1/2 x 7



Products on this page are NOT SUITABLE for unattended equipment unless indicated by symbol. See inside back cover for additional information.

See pages 48 through 71 for OEM direct replacement models.

PSC motors use 5M 370V capacitors unless otherwise indicated.