



Fig. A D3771, D3772, D3758, D3760



Fig. B D3775, D3774, D3752, D3755


- 230 VAC models
- All angle mount bearings. Use rainshield when necessary

Note: Motors on this page have RPM ratings based on 50 Hz power. 60 Hz power will increase RPM approximately 20%.

- Sleeve bearings
- Thermally protected
- UL recognized
- CSA certified

PSC • 50 Hz • OPEN AND TOTALLY ENCLOSED VENTILATION AIR-OVER									
H.P.	Volts	Amps	Rot.	RPM	Model	Fig.	"A" Dim. Inch/MM	Shaft Dim. Inches/MM	Weight Lbs./Kilos
1/6-1/8-1/10	230	.8-.6-.5	D.S.	1350	D3775	B	3.5/89	7.75 x .5 x 7.75 197 x 12.7 x 197	11/5.0
1/4-1/5-1/6	230	1.5-1.1-.8	D.S.	1350	D3774+	B	4.0/102	7.5 x .5 x 7.5 191 x 12.7 x 191	14/6.4
1/3-1/4-1/5	230	2.1-1.5-1.1	D.S.	1350	D3771	A	4.5/114	7.25 x .5 x 7.25 184 x 12.7 x 184	15/6.8
1/2-1/3-1/4	230	3.0-1.9-1.3	D.S.	1350	D3772*	A	4.8/122	7.0 x .5 x 7.0 178 x 12.7 x 178	17/7.7
1/6-1/8-1/10	230	1.2-.8-.6	D.S.	900	D3752	B	4.0/102	7.5 x .5 x 7.5 191 x 12.7 x 191	13/5.9
1/4-1/5-1/6	230	2.0-1.4-1.0	D.S.	900	D3755+	B	4.5/114	7.25 x .5 x 7.25 184 x 12.7 x 184	16/7.3
1/3-1/4-1/5	230	2.6-1.7-1.3	D.S.	900	D3758	A	5.3/135	7.0 x .5 x 6.75 178 x 12.7 x 178	20/9.1
1/2-1/3-1/4	230	4.2-2.2-1.5	D.S.	900	D3760*	A	5.5/140	7.0 x .5 x 7.0 178 x 12.7 x 178	22/9.0

*Uses 10M 370V capacitor
+Includes dust seal



Products on this page are NOT SUITABLE for unattended equipment unless indicated by ► symbol. See inside back cover for additional information.