



Fig. A D6622, D6624, D6626



**Fig. B D6628, D6630, D6631
D6633**



Fig. C D6608, D6610

NEMA 56 FRAME • DRIP PROOF • THREE PHASE RESILIENT BASE • 208-230/460 VOLT • BALL BEARING CONTINUOUS DUTY • REVERSIBLE • UL & CSA CERTIFIED								
H.P.	RPM	FLA	Service Factor	Thermal Protection	Fig.	Model	Shaft Dim.	Ring to Ring Dim.
1/3	1725	1.6/.8	1.35	Auto	A	D6622	5/8 x 2	8.445
1/2	1725	2.0/1.0	1.25	Auto	A	D6624	5/8 x 2	8.945
3/4	1725	2.8/1.4	1.25	Auto	A	D6626	5/8 x 2	9.945
1	1725	3.4/1.7	1.15	Auto	B	D6628	5/8 x 2	9.445
1½	1725	4.6/2.3	1.15	Auto	B	D6630	5/8 x 2	9.945
2	1725	6.2/3.1	1.15	Auto	B	D6631*	5/8 x 2	9.945
3	1725	8.0/4.0	1.10	Auto	B	D6633■	7/8 x 2 3/8	11.445

* 56H Mounting

■ 145T Frame

NEMA 56Y FRAME • THREE PHASE • REVERSIBLE CONDENSER FAN MOTORS • BALL BEARING 208-230/460 VOLT							
H.P.	RPM	FLA	Service Factor	Thermal Protection	Fig.	Model	Shaft Dim.
1	1140	4.0/2.0	1.15	Auto	C	D6608	5/8 x 3 3/4
1½	1140	5.6/2.8	1.15	Auto	C	D6610	5/8 x 3 3/4

Products on this page are NOT SUITABLE for unattended equipment unless indicated by ► symbol. See inside back cover for additional information.