

H.P.	Volts	Amps	RPM	Spd.	Model	Fig.	Type	Mtg.	Dia.	Rot.	"A" Dim	Shaft Dia. and Length	Reference No.
TAPPAN													
73CFM	115-230	.8/5	3000	1	A073 *	A	SP	-	3.3	C.C.W.	-	-	82932, 8251560133
TECUMSEH													
1/15	460	.6	1550	1	D475	D	SP	Stud	3.9	C.C.W.	4-1/2	5/16 x 2-1/2	Tecumseh 810G037A47 5KSP11FG1197CS
TEMPMASTER/OTASCO													
1/5-1/6-1/8	208-230	1.6-1.5 1.3	1400	3	D1033	B	PSC	Base	5.0	D.S.	3-3/4	2-3/4 x 1/2 x 3-1/2	M11730, 322P373 M12100, 322P454
THERMADOR (TRADEWINDS)													
▶ 1/20	115	2.0	1550	1	D1165	E	SP	Stud	3.3	D.S.	3	3-1/2 x 5/16 x 3-1/2	Tradewinds/Blower Motor
▶ 1/100	115	.5	1085	1	D1155	F	SP	Stud	3.3	C.C.W.	2-1/4	1/4 x 1	17-09-679, VQT-90, JA2M087R
THERMAL TRANSFER													
NEW 1/4	115	7.2	1600	1	D1006	G	SP	Base	4.4	C.W.	4-1/8	1/2 X 2-3/4	7108-6544, 66098
TJERNLUND													
1/40	115	1.0	1500	1	D130	C	SP	Stud	3.3	C.W.	3-1/3	5/16 x 4-1/8	7163-6058

• Ball bearing motor

NOTE: Rotation is determined by looking at shaft end. Shaft length is measured from motor face.



Fig. A A073



Fig. C D130



Fig. E D1165



Fig. G D1006




Fig. B D1033



Fig. D D475



Fig. F D1155



Products on this page are NOT SUITABLE for unattended equipment unless indicated by ▶ symbol. See inside back cover for additional information.

PSC motors use 5M 370V capacitors unless otherwise indicated.