


CATALOG NUMBER	OUTPUT RPM	FULL LOAD TORQUE LB.-IN.	INPUT HP	OVERHUNG LOAD LBS.	GEARMOTOR TYPE & FRAME	RATIO TO 1	"XL"	"XH"
M1145023.00	15	208	1/15	407	P243-38	114	10.46	8.96
M1145024.00	30	135	1/15	330	P242-38	52	10.46	8.96
M1145025.00	45	92	1/15	292	P242-38	35	10.46	8.96
M1145026.00	70	61	1/15	256	P242-38	23	10.46	8.96
M1145027.00	97	43	1/15	232	P242-38	16.5	10.46	8.96
M1145028.00	139	30	1/15	208	P242-38	11.5	10.46	8.96
M1145029.00	8	345	1/15	491	P243-38	216	10.46	8.96

05	EXTENDED 3 PT MOUNTING HOLES .14" TO MAKE FLUSH	RLW	6/25/02		TOLERANCES UNLESS SPECIFIED	 ELECTRIC MOTORS GEARMOTORS AND DRIVES	DRAWN	SPV 05/21/94			
04	REV'D NAMEPLATE APPEARANCE FOR ASSEMBLY	BJB	6/25/02	DWF	DEC. INCHES		CHK				
	CLARITY PER ECR 65231				.X ±.1	APPD	DWF 05/21/94				
03	3.50 WAS 3.562, 5.13 WAS 5.19	SPV	06/29/95		.XX ±.03	TITLE	OUTLINE DRAWING				
02	ADDED CAPACITOR MOUNTING SCREW	SPV	06/29/95		.XXX ±.005	P240 GEARMOTOR - 38 FRAME A.C.					
01	REVISED TO NEW STOCK STANDARDS	TMZ	05/15/95		.XXXX ±.0005	MAT'L.	SCALE 5=8				
NO.	REVISION	BY & DATE	CHK	ANG	±1/2"	FINISH	REF				
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT						RFP	CAD FILE	M1030380	SIZE	DRAWING NO.	REV.
						DIST	B	M1030380	B	M1030380	05